

Material Safety Data Sheet

MASTER COLOUR

AE-2 White L.S.

1. Identification of the Substance/Preparation and Company

Product name: Euro Colour Master Colour AE-2 White L.S.
Product Code: 20411130300100
Product Barcode: 8854611100022
Product type: Concentrated Tinter
Supplier: Thainakorn Paint & Chemical Co., Ltd
Address: 91 Ramkumhaeng Rd. Minburi Minburi Bangkok Thailand, 10510
Contact numbers: 66-2916-7714-9
Emergency telephone number: 66-2916-7714-9

2. Composition/Information on Ingredients

Chemical Name	CAS No	EC No	Symbol	%WT
Urea – Aldehyde Resin	50-0-0	-	-	17.0
Titanium Dioxide	13463-67-7	236-675-5	Xn	4.0
Toluene	108-88-3	200-662-2	F, Xi	39.0
Xylene	1330-20-7	215-535-7	Xn	40.0

(Reference to EC directive 67/548/EEC)

3. Hazards Identification

Human health hazards: Harmful by inhalation. Irritating to eyes and skins.

Safety hazards: Flammable. In use, may form flammable/explosive vapor-air mixture.

4. First Aid Measures

Inhalation: Remove to fresh air. Keep patient warm and at rest. If does not rapidly recover, obtain medical attention immediately.

Skin: Wash skin with water using soap if available. If the irritation is persisting, obtain medical attention immediately.

Eye: Immediately flush eye with plenty of water by 15 minutes, holding the eyelids apart. Call for medical attention instantaneously.

Ingestion: Do not induce vomiting. Do not give anything by mouth to unconscious person. Rise mouth with water. Ingest activated charcoal. Obtain medical attention immediately.

5. Fire-Fighting Measures

Suitable Extinguishing Media: Foam (alcohol resistant, carbon dioxide, powders, water spray). Do not allow run-off from fire fighting to enter drains or water courses.

Unsuitable Extinguishing Method: Water jet

Special Hazards due to the Substance, its Decomposition Products or Gases produced by Fire:

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Special Protective Equipment: Appropriate breathing apparatus may be required.

Additional information: Cool closed containers in the vicinity of the source of fire.

6. Accidental Release Measures

Personal precautions: Avoid contact with skin and eyes. Ventilate contaminated area thoroughly. Do not breathe vapor. Extinguish naked flames. Remove ignition sources. No smoking. Avoid sparks. Evacuate the area of all non-essential personnel. Shut off leaks, if possible without personnel risk

Personal protection: Wear neoprene or nitrile rubber gloves, PVC one-piece suit with integral hood. Safety boots-rubber, knee length. Wear full face-piece respirator with organic vapor canister NPF 400. In a confined space, wear self-contained breathing apparatus open circuit type NPF 2000.

Environmental precautions: Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Clean-up methods-small spillage: Absorb or contain liquid with absorbent materials. Shovel up and place in a labeled, sealable container for subsequent safe disposal. Put leaking containers in a labeled drum or over drum. Flush contaminated area with plenty of water. Retain washings as contaminated waste.

Clean-up method-large spillage: Transfer to a labeled, sealable container for product recovery or safe disposal. Treat residues as for small spillage. Do not wash up with solvents.

7. Handling and Storage

Handling: Avoid prolonged or repeated contact with eyes and skins. Do not breathe vapor. Only use in well ventilated areas. Extinguish any naked flames. Remove ignition sources. Avoid sparks. Do not empty into drains.

Handling temperatures: Ambient

Storage: Keep away from direct sunlight and other sources of heat or ignition as well as children. Do not smoke in storage areas. Keep container tightly closed and in a well ventilated place.

Storage temperatures: 5-45 °C

Product transfer: Earth all equipment

Recommended materials: For containers or container linings, use mild steel or stainless steel. For container paints, use zinc silicate.

Unsuitable materials: None specified

8. Exposure Controls/Personal Protection

Engineering control measures: Use local exhaust ventilation.

Occupational Exposure Limits

Substance Name	CAS No.		Limit values	
			ml/m3 (ppm)	mg/m3
Xylene (mixture of isomers)	1330-20-7	TWA	100	-
		STEL	150	-
toluene	108-88-3	TWA	100	-
		STEL	125	-

Respiratory protection: Where local exhaust ventilation is not practicable, wear full face-piece respirator with organic vapor cartridge NPF 20.

Hand protection: Chemical-resistant gloves

Eye protection: Monogoggles.

Body protection: Standard issue work cloths. Safety shoes or chemical resist boots.

9. Physical and Chemical Properties

Physical state:	Vicious Liquid
Color:	White
Odor:	Characteristic
PH:	Not applicable
Solution in water at 20:	Insoluble
Viscosity:	40-60s ISO 2434-1993
Other solubilities:	Most organic solvent
Flash point:	23° C
Density:	1000 g/liter @ 25° C
Autoignition:	370° C

10. Stability/Reactivity

Stability: Stable in room temperature in closed container under normal storage and handling conditions.

Conditions to avoid: Heat, flames and sparks

Material to avoid: Concentrated peroxide may emerge explosion and fire

Hazardous decomposition product: In case of fire carbon monoxide, carbon dioxide nitrogen oxide smoke may be formed.

11. Toxicological Information

Basis for assessment:	Information given is based on product data.
Acute toxicity:	No data is available on the product itself
Eye irritation:	Irritant and maybe reversible damage
Skin irritation:	Slight irritant
Respiratory irritation:	May cause of drowsiness and dizziness.
(Sub) chronic toxicity:	Repeated exposure causes damages on kidney, liver and central nervous.
Reproductive toxicity:	No data available

Human effects: Exposure to component solvent vapor may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.

12. Ecological Information

Ecotoxicity

Acute Toxicity

Chemical Name	Species	Exposure times	Value	Type	Method
Xylene	Daphnia	24 hours	72.8 mg/l	EC50	DIN 38412
	Gloden orfe	48 hours	71 mg/l	LC50	
	Scenedesmus quadricauda	192 hours	21 mg/l	EC50	
	Pseudomonas	18 hours	959 mg/l	EC50	

Mobility : Floats on water. Absorb to soil and has low mobility.

Persistence/ degradation : Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulation : Has the potential to bioaccumulation

13. Disposal Considerations

Waste from residues: Classified as hazardous waste. Dispose of as special waste in compliance with applicable regulations Prevent product from entering drains.

Contaminated packaging: Classified as hazardous waste. Dispose of as special waste in compliance with applicable regulations. Fully drained containers which are drop- and scrape-free can be treated as industrial waste, and can possibly be recycled.

14. Transport Information

UN Number: 1263

UN Class/ Packing Group: 3/III

UN Proper shipping name: Paint

UN Number (sea transport, IMO): N/A

15. Regulatory Information

EC Label name: Paint

EC Symbol: Xn – Harmful

Contents: xylene

2-hydroxyethyl acrylate

EC Risk Phrases: R10 Flammable; R20/21 Harmful by inhalation and in contact with skin R36/38 Irritating to eyes and skins; R43 May cause sensitization by skin contact

EC Safety phrases: S23 Do not breathe vapor; S24 Avoid contact with skin; S36/37 Wear suitable protective clothing and gloves; S46 If swallowed,

seek medical advice immediately and show this container or label where possible; S51 Only use in well ventilated areas

National Regulations:

The Control of Substances Hazardous to Health Regulations 2002

The Manual Handling Operations Regulations 1992

Storage of Packaged Dangerous Substances, HS (G)71

Environmental Protection Act

16. Other Information

Use and restrictions: Car paint for professional use only

Technical contact point: For further information, contact your sales representative or agent.

SDS distribution: The information provided in this document should be made available to all who may handle the product.

Disclaimer: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this document is meant as a description of the safety requirements of our product. It should not therefore be construed as guaranteeing any specific property of the product.

THAINAKORNPAIN and Chemical Co.,Ltd.

91 Ramkhamhaeng Road, Min Buri District,

Bangkok, Thailand 10510

Tel: +66(0) 29167714-9

Fax: +66(0) 25180872

sales@thainakornpaint.com

www.thainakornpaint.com